



PRODUCT INFORMATION

distributed by NITEO™ Products

MAXLIFE™ FUEL SYSTEM CLEANER

DESCRIPTION:

Valvoline™ MaxLife™ Fuel System Cleaner is specially formulated to remove stubborn deposits that rob your high mileage vehicle of fuel economy and performance. Removes harmful deposits from your vehicle's fuel injectors and intake valve that cause hesitation and stumbling on acceleration, knocking, pinging, and higher emissions. MaxLife Fuel System Cleaner also removes deposits from the fuel sending unit, which can cause erratic fuel gauge readings. Contains detergents designed to remove deposits from carburetors.

This multi-purpose cleaner will help clean fuel systems, which in turn helps save gas. It also helps fight fuel line freeze and prevents corrosion in the fuel system. MaxLife Fuel System Cleaner is safe for catalytic converters and oxygen sensors. Contains no alcohol and can be used with all gasoline, gasohol and E-85.

To insure good mixing, add the entire contents to the fuel tank prior to fill up. One bottle treats up to 20 gallons of gasoline.



Part Number	Description	Unit UPC
844762	Valvoline MaxLife Fuel System Cleaner 12/12 oz.	0 74130 83100 1

BENEFITS:

- Helps improve acceleration, power and performance
- Cleans fuel system and injectors
- Eliminates rough idle and hesitation caused by deposits
- Excellent rust control when moisture is present in the fuel system
- Helps restore fuel economy by keeping fuel injectors clean
- Contains no alcohol
- Reduces knock and ping
- Eliminates run-on

FOR MORE INFORMATION, VISIT WWW.NITEOPRODUCTS.COM OR CALL 844-696-4836

This information applies only to products manufactured in the following location(s): USA, Canada

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:
1/27/2015	1/27/2020	3/1/2011	SMW	2

All information herein is believed to be true and correct, but is not to be taken as a representation or warranty, express or implied, including any warranty with respect to merchantability or fitness for any particular purpose. ™Trademark, Niteo, registered in various countries. ©2015, Niteo.



PRODUCT INFORMATION

distributed by NITEO™ Products

TECHNICAL DATA:

Appearance	Clear, Yellow Liquid
Boiling Point	347 °F / 175 °C
Flash Point, °F	120 °F minimum
Specific Gravity	0.806@ 60 °F
VOC Category	NA
VOC/Regulatory Restrictions	None / Flammable Liquid

FOR MORE INFORMATION, VISIT WWW.NITEOPRODUCTS.COM OR CALL 844-696-4836

This information applies only to products manufactured in the following location(s): USA, Canada

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:
1/27/2015	1/27/2020	3/1/2011	SMW	2

All information herein is believed to be true and correct, but is not to be taken as a representation or warranty, express or implied, including any warranty with respect to merchantability or fitness for any particular purpose. ™Trademark, Niteo, registered in various countries. ©2015, Niteo.