



PRODUCT INFORMATION

distributed by NITEO™ Products

MAXLIFE™ POWER STEERING FLUID with STOP LEAK

DESCRIPTION:

Valvoline's **MaxLife Power Steering Fluid with Stop Leak** is a premium power steering fluid that helps maintain superior efficiency and performance of power steering units. Prevents leakage and squealing under severe conditions. Conditions seals, Protects against pump breakdown caused by wear, oxidation and foaming. Performs in subzero temperatures to insure cold weather performance. Will not clog or foam. Helps prevent corrosion, wear and oxidation. Use year-round. Meets GM part number 1050017 (Spec. 9985010), Chrysler Spec. 5931, and Ford Spec. M2C128C & D.

- Replaces material # VV056 SynPower Power Steering Fluid
- This product will help reduce and or eliminate the power steering whine noise associated with some GM Autos as stated in GM Bulletin # 1875699.



Use the fluid recommended in the owner's manual. Some power steering units are designed to use transmission fluid, while others are designed to use power steering fluid. Using the wrong fluid can cause performance deficiencies such as excessive foaming or improper lubrication. Never use power steering fluid in transmissions or as engine oil.

Check the level of the power steering fluid at least once a year. If the power steering fluid is low, check the owner's manual for proper fluid specifications before bringing fluid up to the specified level. Do not overfill.

| Part Number | Description | Unit UPC |
|-------------|--|-----------------|
| VV335 | MaxLife Power Steering Fluid with Stop Leak 6/32 oz. | 0 74130 00335 4 |

BENEFITS:

- A premium semi-synthetic power steering fluid that helps improve performance
- Helps stop squeals and leaks under severe conditions
- Conditions seals
- Protects against corrosion and wear
- Will not clog of foam

FOR MORE INFORMATION, VISIT WWW.NITEOPRODUCTS.COM OR CALL 844-696-4836

This information applies only to products manufactured in the following location(s): USA, Canada

| | | | | |
|---------------------------|------------------|-----------|---------------------------|-------------|
| Effective Date: 3/1/11 | Expiration Date: | Replaces: | Author's Initials: SMW | Pages: 2 |
|---------------------------|------------------|-----------|---------------------------|-------------|

All information herein is believed to be true and correct, but is not to be taken as a representation or warranty, express or implied, including any warranty with respect to merchantability or fitness for any particular purpose. ™Trademark, Niteo, registered in various countries. ©2015, Niteo.



PRODUCT INFORMATION

distributed by NITEO™ Products

TECHNICAL DATA:

| | |
|-------------------|---------------------|
| Appearance | Clear, Amber Liquid |
| Viscosity @ 40°C | 50 cSt maximum |
| Viscosity @ 100°C | 7 cSt minimum |
| Pour Point | -42°C maximum |
| Zinc, ppm | 40 - 60 |

FOR MORE INFORMATION, VISIT WWW.NITEOPRODUCTS.COM OR CALL 844-696-4836

This information applies only to products manufactured in the following location(s): USA, Canada

| | | | | |
|-----------------|------------------|-----------|--------------------|--------|
| Effective Date: | Expiration Date: | Replaces: | Author's Initials: | Pages: |
| 3/1/11 | | | SMW | 2 |

All information herein is believed to be true and correct, but is not to be taken as a representation or warranty, express or implied, including any warranty with respect to merchantability or fitness for any particular purpose. ™Trademark, Niteo, registered in various countries. ©2015, Niteo.